

DISPONIBILITA' DIAMETRI 12 mm. E 15 mm. / AVAILABLE ON STOCK DIAM. 12 mm AND 15 mm.

Diametro Corpo e Stelo	Codice Fx	Rif.Tecnico	Attacchi Corpo e Stelo	Corsa in mm	Spinta in Kg
Diameters Body and Piston rod	Code Fx	Vapsint Code	Fittings Body and Piston Rod	Stroke in mm.	Thrust in Kg.
12 4		124.330.4	rs4-tf12	150	4
15 6		156.150.5	rs3-tz2	45	5
Attacchi Forati		156.165.20	rs3-rs3	55	20
		156.165.25	rs3-rs3	55	25
		156.165.30	rs3-rs3	55	30
		156.165.35	rs3-rs3	55	35
		156.165.40	rs3-rs3	55	40
		156.165.45	rs3-rs3	55	45
		156.165.50	rs3-rs3	55	50
	128	156.180.10	rs3-rs3	65	10
		156.185.2	rs3-tz2	60	2
		156.185.5	rs3-tz2	60	5
		156.185.10	rs3-tz2	60	10
		156.185.15	rs3-tz2	60	15
		156.216.33	rs3-rs3	70	33
		156.225.2	rs3-tz2	80	2
		156.225.5	rs3-tz2	80	5
		156.225.10	rs3-tz2	80	10
		156.225.15	rs3-tz2	80	15
		156.225.20	rs3-tz2	80	20
		156.226.3	rs3-tz2	80	3
	180	156.245.24	rs3- rs3	100	24
	121	156.245.33	rs3a-rs3a	90	33
	171	156.252.35	rs sp-rs3	100	35
		156.265.2	rs3-tz2	100	2
		156.265.5	rs3-tz2	100	5
		156.265.10	rs3-tz2	100	10
		156.265.15	rs3-tz2	100	15
		156.265.20	rs3-tz2	100	20
	182	156.300.30	rs3b- rs3b	115	30
	102	156.303.27	rs3- rs3	110	27
		156.305.2	rs3-tz2	120	2
		156.305.5	rs3-tz2	120	5
		156.305.10	rs3-tz2	120	10
		156.305.15	rs3-tz2	120	15
		156.305.20	rs3-tz2	120	20
	161	156.357.29	rs - fi	160	29
		156.365.5	rs3-tz2	150	5
		156.365.10	rs3-tz2	150	10
		156.365.15	rs3-tz2	150	15
		156.365.20	rs3-tz2	150	20
		156.400.10	rs3-tz2	170	10
		156.400.20	rs3-tz2	170	20
	170	156.410.28	rs sp - rs sp	165	28
	150	156.545.22	rs sp- rs sp	240	22
15 6		156.153.3	tsns-tsns f/f	45	3
Attacchi Snodati		156.153.5	tsns-tsns f/f	45	5
		156.153.8	tsns-tsns f/f	45	8
		156.153.10	tsns-tsns f/f	45	10
		156.155.35	ts4-ts4	40	35
	211	156.155.40	ts1-ts1	40	40
		156.185.5	tsns-tsns f/f	60	5
		156.185.8	tsns-tsns f/f	60	8
		156.185.10	tsns-tsns f/f	60	10
		156.185.12	tsns-tsns f/f	60	12
		156.225.6	tsns-tsns f/f	80	6
		156.225.8	tsns-tsns f/f	80	8
		156.225.12	tsns-tsns f/f	80	12
		156.227.6	tsns-tsns f/f	80	6
		156.227.8	tsns-tsns f/f	80	8
		156.227.10	tsns-tsns f/f	80	10
		156.227.14	tsns-tsns f/f	80	14
		156.247.3	tsns-tsns f/f	90	3
		156.247.5	tsns-tsns f/f	90	5
		156.247.8	tsns-tsns f/f	90	8
		156.247.10	tsns-tsns f/f	90	10
		156.247.12	tsns-tsns f/f	90	12
		156.247.14	tsns-tsns f/f	90	14

DISPONIBILITA' DIAMETRI 12 mm. E 15 mm. / AVAILABLE ON STOCK DIAM. 12 mm AND 15 mm.

Diametro Corpo e Stelo	Codice Fx	Rif.Tecnico	Attacchi Corpo e Stelo	Corsa in mm	Spinta in Kg
		156.247.16	tsns-tsns f/f	90	16
		156.247.20	tsns-tsns f/f	90	20
		156.265.5	ts1-ts1	90	5
		156.265.6	tsns-tsns f/f	95	6
		156.265.7	tsns-tsns f/f	95	7
		156.265.8	tsns-tsns f/f	95	8
		156.265.10	tsns-tsns f/f	95	10
		156.273.4	tsns-tsns f/f	100	4
		156.273.6	tsns-tsns f/f	100	6
		156.273.8	tsns-tsns f/f	100	8
		156.273.10	tsns-tsns f/f	100	10
		156.275.13	ts4-ts4	100	13
	143	156.300.40	ts1- ts1 f/f	100	40
	140	156.305.32	ts1- ts1 f/f	110	32
	142	156.305.49	ts1- ts1 f/f	110	49
		156.310.3	tsns-tsns f/f	120	3
		156.310.5	tsns-tsns f/f	120	5
		156.310.8	tsns-tsns f/f	120	8
		156.310.10	tsns-tsns f/f	120	10
		156.310.12	tsns-tsns f/f	120	12
	186	156.310.13	Ts5-Ts5	120	13
		156.310.14	tsns-tsns f/f	120	14
		156.310.20	tsns-tsns f/f	120	20
		156.315.5	ts4-ts4	115	5
	309	156.345.30	ts1pl-ts1pl f/f	135	30
	141	156.355.25	ts1- ts1 f/f	130	25
	295	156.363.13	tsns-tsns f/f	147	13
		156.370.5	tsns-tsns f/f	150	5
		156.370.8	tsns-tsns f/f	150	8
		156.370.10	tsns-tsns f/f	150	10
		156.370.12	tsns-tsns f/f	150	12
		156.470.4	tsns-tsns f/f	195	4
		156.470.6	tsns-tsns f/f	195	6
		156.470.8	tsns-tsns f/f	195	8
		156.470.10	tsns-tsns f/f	195	10
	41	156.600.16	ts1- ts1 f/f	255	16

DISPONIBILITA' DIAMETRO 18,5 mm. / AVAILABLE ON STOCK DIAMETER 18,5 mm.

Diametro Corpo e Stelo	Codice Fx	Rif.Tecnico	Attacchi Corpo e Stelo	Corsa in mm	Spinta in Kg
Diameters Body and Piston rod	Code Fx	Vapsint Code	Fittings Body and Piston Rod	Stroke in mm.	Thrust in Kg.
19 8 Attacchi Diversi		198.210.18	rs2-fil	70	18
		198.215.18	rs2-fil	70	18
	9	198.232.53	pe - fi	85	53
		198.250.30	rs1-tsns	90	30
	310	198.305.37	rs1-ts1 f	105	37
	173	198.343.54	bf - ts1 f	100	54
	40	198.360.20	rs2- ts1pl	140	20
	192	198.405.27	rs2- ts1 f	165	27
		198.495.15	rs2-tsns f	210	15
	54	198.500.27	rs2- ts1 f	200	27
	53	198.500.55	rs2- ts1 f GF2	200	55
	184	198.525.28	Bf - Ts1pl	205	28
	33	198.545.23	rs1- ts4 f	200	23
	34	198.580.21	rs1- ts4 f	250	21
	84	198.650.30	rs2- ts1pl f	280	30
19 8 Attacchi Forati		198.255.15	rs2-tz	85	15
		198.255.40	rs2-tz	85	40
		198.355.40	rs2-tz	130	40
		198.355.50	rs2-tz	130	50
		198.600.30	rs2-tz	250	30
	4	198.230.40	rs2- rsp	65	40
		198.230.40	rs2-tz	70	40
		198.255.10	rs2-tz	85	10
		198.255.20	rs2-tz	85	20
	1	198.255.30	rs2- tz	85	30
	194	198.255.37	rs1- tf2	85	37
	190	198.255.60	rs1- tf2	80	60
		198.300.30	rs2-tz	100	30
	193	198.320.37	rf3a- tf2	120	37
	191	198.320.37	rs1- tf2	120	37
		198.323.45	rs2-tz	120	45
	31	198.325.25	rs1- rs1	110	25
		198.355.10	rs2-tz	130	10
		198.355.15	rs2-tz	130	15
		198.355.20	rs2-tz	130	20
		198.355.30	rs2-tz	130	30
	2	198.355.67	rs2- tz	130	67
		198.400.10	rs2-tz	150	10
		198.400.15	rs2-tz	150	15
		198.400.20	rs2-tz	150	20
		198.400.30	rs2-tz	150	30
		198.485.50	rs2-tz	200	50
		198.500.10	rs2-tz	200	10
		198.500.13	rs2-rs2	200	13
		198.500.15	rs2-tz	200	15
		198.500.18	rs2-rs2	200	18
		198.500.18	rs2-tz	200	18
		198.500.20	rs2-tz	200	20
		198.500.30	rs2-tz	200	30
		198.500.40	rs2-tz	200	40
	50	198.500.47	rs2- tz	200	47
	20	198.500.47	rslu- rs2	200	47
	60	198.520.22	rs2- tz	215	22
		198.550.10	rs2-tz	225	10
		198.550.15	rs2-tz	225	15
		198.550.20	rs2-tz	225	20
	16	198.550.22	rsp- tz	225	22
		198.550.30	rs2-tz	225	30
	10	198.550.35	rs2- tz	225	35
	22	198.550.38	rsp- tz	225	38
	52	198.550.39	rs2- tz	225	39
		198.550.50	rs2-tz	225	50
		198.600.10	rs2-tz	250	10

DISPONIBILITA' DIAMETRO 18,5 mm. / AVAILABLE ON STOCK DIAMETER 18,5 mm.

		198.600.15	rs2-tz	250	15
		198.600.20	rs2-tz	250	20
11		198.600.22	rs2- tz	250	22
		198.600.25	rs2-tz	250	25
13		198.600.31	rs2- tz	250	31
		198.600.35	rs2-tz	250	35
18		198.600.36	rs2- tz	250	36
12		198.600.40	rs2- tz	250	40
		198.600.45	rs2-tz	250	45
82		198.600.46	rs2- tz	250	46
		198.600.50	rs2-tz	250	50
83		198.600.55	rs2- tz	250	55
35		198.615.22	rs3p- tz1p	265	22
89		198.650.30	rs2- rs2	285	30
130		198.695.22	rs2- rs2	300	22
151		198.700.40	rs2 - rs2	300	40
		198.700.50	rs2-tz	300	50
19 8 Attacchi Snodati	305	198.470.57	ts1pl-ts1pl f/f	190	57
		198.210.50	ts1-ts1	60	50
		198.255.30	tsns-tsns f/f	85	30
	215	198.255.50	ts1-ts1	85	50
	216	198.255.63	ts1-ts1	85	63
	36	198.265.37	ts1pl-ts1 f/f	94	37
	7	198.267.44	ts4- ts4 f/f	85	44
		198.275.10	tsns-tsns f/f	95	10
	149	198.275.52	ts1-ts1	100	52
	148	198.280.49	ts1pl-ts1pl f/f	100	49
	43	198.280.50	ts1-ts1	105	50
	272	198.280.52	ts1pl-ts1pl f/f	95	52
	44	198.280.60	ts1-ts1	102	60
	105	198.290.40	ts1pl-ts1pl f/f	105	40
	179	198.290.64	Ts5-Ts5	100	64
	157	198.295.65	ts1pl-ts1pl f/f	110	65
	218	198.300.56	ts1- ts1 f/f	100	56
	235	198.310.40	ts1pl-ts1pl f/f	105	40
	38	198.310.58	ts1-ts1	110	58
	176	198.315.58	Ts5-Ts5	120	58
	172	198.330.68	ts1-ts1 f/f	120	68
	6	198.335.34	ts4- ts4 f/f	115	34
	47	198.345.62	ts1pl-ts1pl f/f	125	62
	177	198.348.32	ts1pl-ts1pl f/f	100	32
	313	198.355.10	tsns-tsns f/f	140	10
	286	198.355.35	ts5-ts5 f/f	120	35
	1000	198.362.66	ts1-ts1	130	66
	311	198.362.80	ts1-ts1 f/f	130	80
	175	198.365.11	ts1pl-ts1pl f/f	125	11
	181	198.370.40	ts1pl-ts1pl f/f	140	40
	236	198.375.61	ts1pl-ts1pl f/f	145	61
	46	198.380.56	tspns-tspns	145	56
	224	198.390.18	ts1pl-tspns	158	18
		198.400.10	tsns-tsns f/f	150	10
		198.400.20	tsns-tsns f/f	150	20
	32	198.400.30	ts1pl-ts1pl f/f	160	30
	156	198.400.52	ts1pl-ts1pl f/f	164	52
	118	198.410.34	ts1pl-ts1pl f/f	170	34
	103	198.415.64	ts1- ts1 f/f	155	64
	109	198.420.50	ts1pl-ts1pl f/f	160	50
	261	198.428.37	ts5-ts5 f/f	170	37
	57	198.430.33	ts1pl-ts1pl f/f	175	33
	312	198.435.12	ts1pl-ts1pl f/f	160	12
	107	198.435.48	ts1pl-ts1pl f/f	170	48
	42	198.440.37	ts1pl-ts1pl f/f	175	37
	213	198.440.46	ts1pl-ts1pl f/f	175	46
	260	198.440.60	ts1-ts1	175	60
	29	198.445.30	ts1pl-ts1pl f/f	182	30

DISPONIBILITA' DIAMETRO 18,5 mm. / AVAILABLE ON STOCK DIAMETER 18,5 mm.

232	198.450.45	ts1pl-ts1pl f/f	180	45
297	198.453.55	ts5-ts1pl f/f	181	55
240	198.455.35	ts1pl-ts1pl f/f	165	35
207	198.455.38	ts1pl-ts1pl f/f	162	38
225	198.455.68	ts1pl-ts1pl f/f	175	68
115	198.455.74	ts1-ts1 f/f	175	74
97	198.460.30	ts1pl-ts1pl f/f	170	30
93	198.460.38	ts1pl-ts1pl f/f	180	38
299	198.465.44	tspm6-ts5 f/f	173	44
221	198.465.65	ts1-ts1 f/f	145	65
200	198.468.32	ts1pl-ts1pl f/f	195	32
	198.470.20	ts1-ts1 f/f	190	20
308	198.470.38	ts1pl-ts5 f/f	197	38
106	198.470.39	ts1pl-ts1pl f/f	190	39
228	198.470.60	ts1pl-ts1pl f/f	190	60
206	198.475.33	ts1pl-ts1pl f/f	185	33
19	198.475.42	ts1pl-ts1pl f/f	185	42
237	198.475.48	ts5-tspns	175	48
306	198.478.55	tspm6-ts1pl f/f	190	55
3	198.482.30	ts1pl-ts1pl f/f	200	30
197	198.485.45	ts1pl-ts1pl f/f	195	45
152	198.485.53	ts1pl-ts1pl f/f	185	53
214	198.485.53	ts1pl-ts1pl f/f	200	53
129	198.485.64	ts1-ts1 f/f	190	64
230	198.490.23	ts1pl-ts1pl f/f	200	23
263	198.490.51	ts1pl-tspns f/f	190	51
285	198.490.53	ts5-ts5 f/f	199	53
63	198.495.33	ts1pl-tspns f/f	210	33
122	198.495.46	ts1- ts1 f/f	180	46
262	198.495.50	ts1pl-tspns f/f	200	50
51	198.500.27	ts1- ts1 f/f	200	27
226	198.500.28	ts1pl-ts1	205	28
66	198.500.28	tspns-ts1	205	28
90	198.500.35	ts1- ts1 f/f	200	35
55	198.500.35	ts1pl-ts1pl f/f	205	35
65	198.500.35	tspns-ts1	210	35
159	198.500.42	ts1pl-ts1	210	42
146	198.500.42	Tspns-Ts1	210	42
315	198.500.45	tspm6-ts5 f/f	210	45
111	198.500.46	ts1pl-ts1pl f/f	210	46
273	198.500.50	ts1pl-ts1	210	50
304	198.500.50	ts5-ts1 f/f	210	50
58	198.500.50	tspns-ts1pl f/f	210	50
112	198.500.58	ts1pl-ts1pl f/f	210	58
145	198.500.63	tspns-ts1	210	63
212	198.505.25	ts1pl-ts1pl f/f	210	25
241	198.505.38	ts1pl-ts1pl f/f	215	38
5	198.505.43	ts4- ts4 f/f	210	43
203	198.505.52	ts1-ts1 f/f	205	52
223	198.510.25	ts1pl-ts1pl f/f	220	25
289	198.510.36	ts5-ts1pl f/f	210	36
202	198.510.42	ts1pl-ts1pl f/f	210	42
185	198.510.47	Ts1pl-Ts5	205	47
281	198.510.47	ts5-ts1pl	205	47
291	198.510.60	ts1pl-ts1pl f/f	205	60
76	198.510.60	tspns-tspns	205	60
62	198.515.42	ts1-ts1pl	215	42
62	198.515.42	ts1-ts1pl	215	42
72	198.515.55	ts1- ts1 f/f	210	55
293	198.519.59	ts1pl-ts1pl f/f	183	59
294	198.519.63	ts1pl-ts1pl f/f	183	63
104	198.520.36	ts1pl-ts1pl f/f	220	36
201	198.520.36	ts1pl-ts1pl f/f	200	36
205	198.520.58	ts1-ts1 f/f	215	58
37	198.525.30	ts1pl-ts1pl f/f	220	30
131	198.525.35	ts1pl-ts1pl f/f	220	35

DISPONIBILITA' DIAMETRO 18,5 mm. / AVAILABLE ON STOCK DIAMETER 18,5 mm.

45	198.525.38	ts1pl-ts1pl f/f	215	38
227	198.525.45	ts1pl-ts1pl f/f	215	45
24	198.525.49	ts1- ts1 f/f	250	49
174	198.525.53	Ts5-Ts5	175	53
303	198.525.53	Ts5-Ts5	205	53
302	198.525.55	tspm6-tspm6	205	55
80	198.525.66	ts1-ts1	215	66
125	198.530.40	ts1pl-ts1pl f/f	215	40
71	198.535.45	ts1- ts1 f/f	220	45
219	198.535.48	ts1pl-ts1pl f/f	250	48
133	198.535.51	tspns-tspns	225	51
21	198.540.30	ts1- ts1 f/f	200	30
75	198.540.35	ts1pl-ts1pl f/f	205	35
183	198.540.40	ts1pl-ts1pl f/f	220	40
160	198.545.30	ts1- ts1 f/f	225	30
280	198.545.59	ts1pl-ts1pl f/f	200	59
78	198.545.59	tspns-tspns	200	59
73	198.550.41	ts1- ts1	220	41
307	198.550.62	ts1pl-ts1pl f/f	205	62
162	198.552.36	ts1- ts1 f/f	240	36
163	198.552.46	ts1- ts1 f/f	240	46
217	198.552.56	ts1pl- ts1 f/f	225	56
314	198.555.38	tsns-tsns f/f	240	38
220	198.555.47	tspns-ts1pl f/f	235	47
135	198.555.51	ts1pl-ts1	220	51
234	198.555.55	ts1-ts1	210	55
300	198.560.50	ts1pl-ts1pl f/f	193	50
196	198.560.53	ts1pl-ts1pl f/f	193	53
136	198.560.73	ts1pl-ts1pl f/f	215	73
77	198.565.42	ts1pl-ts1pl f/f	180	42
288	198.568.54	ts1pl-ts1pl f/f	210	54
27	198.570.21	ts1- ts1 f/f	220	21
25	198.570.28	ts1pl-ts1pl f/f	220	28
124	198.570.31	ts1pl-ts1pl f/f	225	31
87	198.575.38	ts1pl-ts1pl f/f	245	38
144	198.575.50	ts1pl-ts1	230	50
153	198.575.50	tspns-ts1	230	50
126	198.577.32	ts1pl-ts1pl f/f	240	32
239	198.580.53	ts1pl-ts1pl f/f	220	53
56	198.583.42	ts1pl-ts1pl f/f	250	42
231	198.585.31	ts1pl-ts1pl f/f	230	31
26	198.590.27	ts1pl-ts1pl f/f	240	27
88	198.590.48	ts1pl-ts1pl f/f	250	48
120	198.595.36	ts1- ts1 c/sn M8	240	36
8	198.595.38	ts1pl-ts1pl c/fast	250	38
17	198.595.41	ts1pl-ts1pl f/f	240	41
	198.600.10	tsns-tsns f/f	250	10
101	198.600.29	ts1pl-ts1pl f/f	240	29
59	198.600.30	ts1pl-ts1pl f/f	255	30
166	198.600.30	tspns-ts1pl f/f	255	30
2000	198.600.36	ts1pl-tspns f/f	240	36
283	198.600.44	ts1pl-ts1pl f/f	260	44
116	198.600.51	ts1- ts1 f/f	225	51
117	198.600.51	ts1pl-ts1pl c/fast	270	51
110	198.610.23	ts1pl-ts1pl c/fast	250	23
85	198.610.35	ts1pl-ts1pl f/f	245	35
208	198.610.60	ts1pl-ts1pl f/f	215	60
70	198.615.60	ts2- ts2 f/f	250	60
91	198.622.54	ts1- ts1 f/f	250	54
98	198.625.36	ts1pl-ts1pl f/f	280	36
229	198.625.57	ts1pl-ts1pl f/f	260	57
301	198.625.60	ts1pl-ts1pl f/f	215	60
28	198.630.33	ts1pl-tspns	270	33
282	198.630.44	ts1pl-tspm6	280	44
92	198.640.16	ts1pl-ts1pl f/f	260	16
100	198.640.47	ts1- ts1 f/f	210	47

DISPONIBILITA' DIAMETRO 18,5 mm. / AVAILABLE ON STOCK DIAMETER 18,5 mm.

	188	198.640.51	ts1pl-tspm6	265	51
	154	198.647.45	ts1pl-ts1pl f/f	275	45
	99	198.655.41	ts1pl-ts1pl f/f	275	41
	39	198.670.21	ts4- ts4 f/f	285	21
	195	198.670.37	ts1pl-ts1pl f/f	280	37
	61	198.675.24	ts1pl-ts1pl f/f	275	24
	132	198.675.44	ts1pl-ts1pl f/f	280	44
	209	198.690.47	ts1pl-ts1pl f/f	255	47
	108	198.690.62	ts1pl-ts1pl f/f	300	62
	86	198.695.67	ts1-ts1	250	67
	74	198.700.37	ts1- ts1 f/f	250	37
	290	198.715.16	ts1pl-tspm6	312	16
	158	198.715.33	ts1pl-tspns	315	33
	155	198.725.28	ts1pl-tspns f/f	325	28
	298	198.732.35	ts1pl-tspm6	320	35
1910	233	1910.195.110	ts1-ts1	58	110
	178	1910.595.38	ts1pl-ts1pl f/f	220	38
		1910.690.35	ba2-bs2	300	35
		1910.690.50	ba2-bs2	300	50
		1910.690.60	ba2-bs2	300	60

DISPONIBILITA' DIAMETRO 22 mm. / AVAILABLE ON STOCK DIAMETER 22 mm.

Diametro Corpo e Stelo	Codice Fx	Rif.Tecnico	Attacchi Corpo e Stelo	Corsa in mm	Spinta in Kg
Diameters Body and Piston rod	Code Fx	Vapsint Code	Fittings Body and Piston Rod	Stroke in mm.	Thrust in Kg.
2210		2210.285.100	rs2-tz	100	100
		2210.323.100	rs2-tz	120	100
		2210.385.115	rs2-tz	150	115
		2210.400.80	rs2-tz	155	80
		2210.400.100	rf2-bs1	160	100
		2210.415.70	rf2-tf1	160	70
		2210.415.80	rf2-tf1	160	80
		2210.415.80	ts1pl-ts1pl f/f	160	80
		2210.415.100	rf2-tf1	160	100
		2210.415.100	ts1pl-ts1pl f/f	160	100
		2210.415.110	rf2-tf1	160	110
		2210.415.110	ts1pl-ts1pl f/f	160	110
		2210.415.125	rf2-tf1	160	125
		2210.415.145	rf2-tf1	160	145
	64	2210.450.54	ts1-ts1 f/f	170	54
		2210.485.50	rs2-tz	200	50
	164	2210.490.40	rf2- ts2 /f	190	40
	238	2210.550.85	ts1-ts1	225	85
	123	2210.570.65	ts1- ts1 f/f	220	65
		2210.585.50	rs2-tz	250	50
		2210.585.80	rs2-tz	250	80
		2210.600.60	rf2-bs1	250	60
		2210.600.80	rf2-bs1	250	80
		2210.600.110	rf2-bs1	250	110
	113	2210.605.63	ts1- ts1 f/f	200	63
	222	2210.605.85	ts1pl-ts1pl f/f	210	85
		2210.685.25	rs2-tz	300	25
		2210.685.30	rs2-tz	300	30
		2210.685.50	rs2-tz	300	50
		2210.685.80	rs2-tz	300	80
	114	2210.700.29	ts1- ts1 f/f	300	29
		2210.700.35	rf2-bs1	300	35
		2210.700.55	rf2-bs1	300	55
		2210.700.70	rf2-bs1	300	70
	316	2210.700.110	ts1pl-ts1pl f/f	200	110
	284	2210.727.82	ts1pl-ts1pl f/f	230	82
	296	2210.735.72	ts1pl-ts1pl f/f	328	72
		2210.785.30	rs2-tz	350	30
		2210.785.50	rs2-tz	350	50
		2210.785.80	rs2-tz	350	80
		2210.800.80	rf2-bs1	350	80
		2210.800.90	rf2-bs1	350	90
	292	2210.850.67	ts1pl-ts1pl f/f	350	67
	210	2210.865.37	ts1pl-ts1pl f/f	355	37
		2210.885.30	rs2-tz	400	30
		2210.885.50	rs2-tz	400	50
		2210.885.80	rs2-tz	400	80
	30	2210.985.35	rs1- rs1	410	35

DISPONIBILITA' DIAMETRO 28 mm. / AVAILABLE ON STOCK DIAMETER 28 mm.

Diametro Corpo e Stelo	Codice Fx	Rif.Tecnico	Attacchi Corpo e Stelo	Corsa in mm	Spinta in Kg
Diameters Body and Piston rod	Code Fx	Vapsint Code	Fittings Body and Piston Rod	Stroke in mm.	Thrust in Kg.
2810	127	2810.590.78	tspns-tspns	210	78
		2810.600.60	rf5- bs1	250	60
		2810.600.80	rf5- bs1	250	80
	Ind 1	2810.700.35	rf5- bs1	300	35
	Ind 3	2810.700.45	rf5- bs1	300	45
		2810.700.50	rf5- bs1	300	50
		2810.700.55	rf5- bs1	300	55
	Ind 2	2810.700.70	rf5- bs1	300	70
		2810.700.80	rf5- bs1	300	80
		2810.700.100	rf5- bs1	300	100
	Ind 4	2810.800.40	rf5- bs1	350	40
		2810.800.50	rf5- bs1	350	50
		2810.800.60	rf5- bs1	350	60
		2810.800.70	rf5- bs1	350	70
		2810.800.80	rf5- bs1	350	80
2814	165	2814.275.150	Ts2-Ts2	85	150
	287	2814.320.116	Ts2-Ts2	92	116
		2814.700.80	rf5- bs1	300	80
		2814.700.100	rf5- bs1	300	100
		2814.700.130	rf5- bs1	300	130
		2814.800.80	rf5- bs1	350	80
		2814.800.90	rf5- bs1	350	90
		2814.800.100	rf5- bs1	350	100
		2814.800.130	rf5- bs1	350	130
		2814.800.150	rf5- bs1	350	150
		2814.900.70	rf5- bs1	400	70
		2814.900.90	rf5- bs1	400	90
		2814.900.100	rf5- bs1	400	100
		2814.900.150	rf5- bs1	400	150
		2814.900.200	rf5- bs1	400	200
		2814.1190.100	rf5- bs1	550	100
		2814.1190.120	rf5- bs1	550	120
		2814.1190.150	rf5- bs1	550	150